CircuitPython Libraries on Linux and Orange Pi

Created by lady ada

https://learn.adafruit.com/circuitpython-on-orangepi-linux

Last updated on 2024-03-08 03:03:37 PM EST

Table of Contents

Overview 5

- Why CircuitPython?
- CircuitPython on Microcontrollers
- CircuitPython Libraries on Desktop Linux

CircuitPython & OrangePi 7

- CircuitPython on Linux & Orange Pi
- Wait, isn't there already something that does this - WiringOP?
- What about other Linux SBCs or other Orange Pi's?

Orange Pi PC Setup 8

- Install ARMbian on your Orange Pi
- Logging in
- Install Python and set Python 3 to Default
- Install libgpiod
- Update Your Board and Python
- Enable UART, I2C and SPI
- Install Python libraries

Orange Pi R1 Setup 15

- Install ARMbian on your Orange Pi
- Connecting the GPIO/Debug Header
- Prepare the header strip:
- Place the header:
- And Solder!
- You're done!
- Logging in using Serial
- Connecting using DHCP and SSH
- MacOS/Linux
- Windows
- Set your Python install to Python 3 Default
- Install libgpiod
- Install Required pip3 Modules
- Update Your Board and Python
- Enable UART, I2C and SPI
- Install Python libraries

Digital I/O 26

- Parts Used
- Wiring
- Blinky Time!
- Button It Up

I2C Sensors & Devices 31

- Parts Used
- Wiring
- Install the CircuitPython BME280 Library
- Run that code!

SPI Sensors & Devices 37

- Parts Used

• Wiring
• Install the CircuitPython MAX31855 Library
• Run that code!

UART / Serial 43

• The Easy Way - An External USB-Serial Converter
• The Hard Way - Using Built-in UART
• Install the CircuitPython GPS Library
• Run that code!

More To Come! 49

FAQ & Troubleshooting 50

• Update Blinka/Platform Libraries

Overview

This guide describes using CircuitPython -libraries- on small Linux computers, running under regular Python. It is not about running the CircuitPython firmware itself on those boards.



Here at Adafruit we're always looking for ways to make making easier - whether that's making breakout boards for hard-to-solder sensors or writing libraries to simplify motor control. Our new favorite way to program is **CircuitPython**.

Why CircuitPython?

CircuitPython is a variant of MicroPython, a very small version of Python that can fit on a microcontroller. Python is the fastest-growing programming language. It's taught in schools, used in coding bootcamps, popular with scientists and of course programmers at companies use it a lot!

CircuitPython adds the Circuit part to the Python part. It lets you program in Python and talk to Circuitry like sensors, motors, and LEDs!

CircuitPython on Microcontrollers

CircuitPython runs on microcontroller boards, such as our Feather, Metro, QT Py, and ItsyBitsy boards, using a variety of chips, such as the MicroChip SAMD21 SAMD51, the

Raspberry Pi RP2040, the Nordic nRF52840, and the Espressif ESP32-S2 and ESP32-S3.

All of these chips have something in common - they are microcontrollers with hardware peripherals like SPI, I2C, ADCs etc. We squeeze Python into 'em and can then make the project portable.

But...sometimes you want to do more than a microcontroller can do. Like HDMI video output, or camera capture, or serving up a website, or just something that takes more memory and computing than a microcontroller board can do...

CircuitPython Libraries on Desktop Linux

By adding a software layer, you can use CircuitPython hardware control capabilities with "regular Python", as found on your desktop or single-board Linux computer/ There are tons of projects, libraries and example code for CircuitPython on microcontrollers, and thanks to the flexibility and power of Python its' pretty easy to get that code working on micro-computers like the Raspberry Pi or other single-board Linux computers with GPIO pins available.

You'll use a special library called **adafruit_blinka** (https://adafru.it/BJS) (named after Blinka, the CircuitPython mascot (https://adafru.it/BJT)) that provides a layer that translates the CircuitPython hardware API to whatever library the Linux board provides. For example, on Raspberry Pi we use the python RPi.GPIO (https://adafru.it/BJU) library. For any I2C interfacing we'll use ioctl messages to the `/dev/i2c` device. For SPI we'll use the `spidev` python library, etc. These details don't matter so much because they all happen underneath the **adafruit_blinka** layer.

The upshot is that most code we write for CircuitPython will be instantly and easily runnable on Linux computers like Raspberry Pi.

In particular, you'll be able to use all of our device drivers - the sensors, led controllers, motor drivers, HATs, bonnets, etc. And nearly all of these use I2C or SPI!

The rest of this guide describes how to install and set up Blinka, and then how to use it to run CircuitPython code to control hardware.

CircuitPython & OrangePi

CircuitPython on Linux & Orange Pi

The next obvious step is to bring CircuitPython **back** to 'desktop Python'. We've got tons of projects, libraries and example code for CircuitPython on microcontrollers, and thanks to the flexibility and power of Python its pretty easy to get it working with micro-computers like Orange Pi or other 'Linux with GPIO pins available' single board computers.

We'll use a special library called **adafruit_blinka** (https://adafru.it/BJS) (named after Blinka, the CircuitPython mascot (https://adafru.it/BJT)) to provide the layer that translates the CircuitPython hardware API to whatever library the Linux board provides. For example, on Orange Pi we use the python **libgpiod** bindings. For any I2C interfacing we'll use ioctl messages to the `/dev/i2c` device. For SPI we'll use the `spidev` python library, etc. These details don't matter so much because they all happen underneath the **adafruit_blinka** layer.

The upshot is that any code we have for CircuitPython will be instantly and easily runnable on Linux computers like Orange Pi.

In particular, we'll be able to use all of our device drivers - the sensors, led controllers, motor drivers, HATs, bonnets, etc. And nearly all of these use I2C or SPI!

Wait, isn't there already something that does this - WiringOP?

WiringOP, a modification of WiringPi, is for GPIO usage only, it doesn't work well for various I2C or SPI devices.

By letting you use CircuitPython on Raspberry Pi via **adafruit_blinka**, you can unlock all of the drivers and example code we wrote! And you can keep using WiringOP for pins, buttons and LEDs. We save time and effort so we can focus on getting code that works in one place, and you get to reuse all the code we've written already.

Right now, Blinka only supports the Orange Pi PC (because that's the only board we've got for testing).

What about other Linux SBCs or other Orange Pi's?

Yep! Blinka can easily be updated to add other boards. We've started with the one we've got, so we could test it thoroughly. If you have an OrangePi or other SBC board you'd like to adapt check out the adafruit_blinka code on github (https://adafru.it/BJX), pull requests are welcome as there's a ton of different Linux boards out there!

Orange Pi PC Setup

This page is for the Orange Pi PC only!

Once armbian is installed, its easy to tell what board you have, simply **cat /etc/armbian-release** and look for `BOARD_NAME`

```
root@orangepipc:/home/pi# cat /etc/armbian-release
# PLEASE DO NOT EDIT THIS FILE
BOARD=orangepipc
BOARD_NAME="Orange Pi PC"
BOARDFAMILY=sun8i
VERSION=5.65
LINUXFAMILY=sunxi
BRANCH=next
ARCH=arm
IMAGE_TYPE=stable
BOARD_TYPE=conf
INITRD_ARCH=arm
KERNEL_IMAGE_TYPE=zImage
root@orangepipc:/home/pi#
```

Install ARMbian on your Orange Pi

We're only going to be using armbian, other distros could be made to work but you'd probably need to figure out how to detect the platform since we rely on `/etc/armbian-release` existing.

Download and install the latest armbian, for example we're using https://www.armbian.com/orange-pi-pc-plus/ (https://adafru.it/Dbx)

There's some documentation to get started at https://docs.armbian.com/User-Guide_Getting-Started/ (https://adafru.it/Dby)

Blinka only supports ARMbian because that's the most stable OS we could find and it's easy to detect which board you have



We've found the easiest way to connect is through a console cable, wired to the debug port, and then on your computer, use a serial monitor at 115200 baud.

Logging in

USB to TTL Serial Cable - Debug / Console Cable for Raspberry Pi
The cable is easiest way ever to connect to your microcontroller/Raspberry Pi/WiFi router serial console port. Inside the big USB plug is a USB<->Serial conversion chip and at...
https://www.adafruit.com/product/954



Once powered correctly and with the right SD card you should get a login prompt



After logging in you may be asked to create a new username, we recommend **pi** - if our instructions end up adding gpio access for the pi user, you can copy and paste em



Once installed, you may want to enable mdns so you can `ssh pi@orangepipc` instead of needing to know the IP address:

- `sudo apt-get install avahi-daemon`

then **reboot**

Install Python and set Python 3 to Default

There's a few ways to do this, we recommend something like this

```
sudo apt-get install -y python3 git python3-pip
sudo update-alternatives --install /usr/bin/python python /usr/bin/python2.7 1
sudo update-alternatives --install /usr/bin/python python /usr/bin/python3.5 2
sudo update-alternatives --config python
```

Of course change the version numbers if newer Python is distributed

Install libgpiod

libgpiod is what we use for gpio toggling. To install run this command:

```
sudo apt-get install libgpiod2 python3-libgpiod
pip3 install gpiod
```

After installation you should be able to `import gpiod` from within Python3



Update Your Board and Python

Run the standard updates:

`sudo apt-get update`

`sudo apt-get upgrade`

and

`sudo pip3 install --upgrade setuptools`

Update all your python 3 packages with

`pip3 freeze - local | grep -v '^\-e' | cut -d = -f 1 | xargs -n1 pip3 install -U`

and

```
sudo bash
```

```
pip3 freeze - local | grep -v '^\-e' | cut -d = -f 1 | xargs -n1 pip3 install -U
```

Enable UART, I2C and SPI

A vast number of our CircuitPython drivers use UART, I2C and SPI for interfacing so you'll want to get those enabled.

You only have to do this once per board but by default all three interfaces are disabled!



Install the support software with

```
sudo apt-get install -y python-smbus python-dev i2c-tools
sudo adduser pi i2c
```



Read **/etc/armbian-release** to figure out your board family, in this case its a **sun8i**

Edit **/boot/armbianEnv.txt** and add these lines at the end, adjusting the `overlay_prefix` for your particular board

```
overlay_prefix=sun8i-h3
overlays=uart3 i2c0 spi-spidev
param_spidev_spi_bus=0
```



Once you're done with both and have rebooted, verify you have the I2C and SPI devices with the command `ls /dev/i2c* /dev/spi*`

You should see at least one i2c device and one spi device







You can test to see what I2C addresses are connected by running `sudo i2cdetect -y 0` (on **PA11/PA12**) or `sudo i2cdetect -y 1` (on **PA18/PA19**)

In this case I do have a sensor on the 'standard' i2c port i2c-0 under address 0x77

You can also install WiringOP and then run `gpio readall` to see the MUX status. If you see **ALT3** next to a pin, its a plain GPIO. If you see **ALT4** or **ALT5**, its an SPI/I2C/UART peripheral



Install Python libraries

Now you're ready to install all the python support

Run the following command to install **adafruit_blinka**

```
pip3 install adafruit-blinka
```



The computer will install a few different libraries such as `adafruit-pureio` (our ioctl-only i2c library), `spidev` (for SPI interfacing), `Adafruit-GPIO` (for detecting your board) and of course `adafruit-blinka`

That's pretty much it! You're now ready to test.

Create a new file called **blinkatest.py** with **nano** or your favorite text editor and put the following in:

```
import board
import digitalio
import busio

print("Hello blinka!")

# Try to great a Digital input
pin = digitalio.DigitalInOut(board.PA6)
print("Digital IO ok!")

# Try to create an I2C device
i2c = busio.I2C(board.SCL, board.SDA)
print("I2C ok!")

# Try to create an SPI device
spi = busio.SPI(board.SCLK, board.MOSI, board.MISO)
print("SPI ok!")

print("done!")
```

Save it and run at the command line with

```
sudo python3 blinkatest.py
```

You should see the following, indicating digital i/o, I2C and SPI all worked



Orange Pi R1 Setup

This page is for the Orange Pi R1 only!

Once armbian is installed, its easy to tell what board you have, simply **cat /etc/armbian-release** and look for `BOARD_NAME`

```
root@orangepi:/home/pi# cat /etc/armbian-release
# PLEASE DO NOT EDIT THIS FILE
BOARD=orangepi-r1
BOARD_NAME="Orange Pi R1"
BOARDFAMILY=sun8i
VERSION=5.83
LINUXFAMILY=sunxi
BRANCH=next
ARCH=arm
IMAGE_TYPE=stable
BOARD_TYPE=conf
INITRD_ARCH=arm
KERNEL_IMAGE_TYPE=zImage
root@orangepi:/home/pi#
```

Install ARMbian on your Orange Pi

We're only going to be using armbian, other distros could be made to work but you'd probably need to figure out how to detect the platform since we rely on `/etc/armbian-release` existing.

Download and install the latest armbian, for example we're using https://www.armbian.com/orange-pi-r1/ (https://adafru.it/EYl)

There's some documentation to get started at https://docs.armbian.com/User-Guide_Getting-Started/ (https://adafru.it/Dby)

Blinka only supports ARMbian because that's the most stable OS we could find and it's easy to detect which board you have



We've found the easiest way to connect is through a console cable, wired to the debug port, and then on your computer, use a serial monitor at 115200 baud. For the Orange Pi R1, you will also need to solder a header for debugging and GPIO access to the Orange Pi R1.



Color Coded Header for Raspberry Pi
Here's a snazzy accessory for your Raspberry Pi Zero or Zero W, a color-coded 2x20 header! This Color Coded Header takes the mystery out of your Raspberry...
https://www.adafruit.com/product/3907

Connecting the GPIO/Debug Header

Because the Orange Pi R1 does not come with any GPIO headers, you will need to solder one in order to connect breakout boards.



Prepare the header strip:

Cut the strip to length. You will want to make a cut to the side of the blue strip that is closer to the center. After cutting, you should have one piece that is 2x13 pins and another that is 2x7 pins.



Place the header:

Because the ethernet ports are on the tall side, we found that placing a small object under the header such as a small piece of foam works well.



And Solder!

Be sure to solder all pins for reliable electrical contact.

(For tips on soldering, be sure to check out our Guide to Excellent Soldering (https://adafru.it/aTk)).



Check your solder joints visually and continue onto the next steps

You're done!

Continue on to the next steps.

Logging in using Serial

To log in through serial, you will need to connect a USB to TTL Serial cable up to the Orange Pi. You may also need to install some software. Be sure to check out our Adafruit's Raspberry Pi Lesson 5. Using a Console Cable (https://adafru.it/kgF) guide. Although it is written for a Raspberry Pi, the drivers and cable connection should be the same.

USB to TTL Serial Cable - Debug / Console Cable for Raspberry Pi

The cable is easiest way ever to connect to your microcontroller/Raspberry Pi/WiFi router serial console port. Inside the big USB plug is a USB<->Serial conversion chip and at...

https://www.adafruit.com/product/954



Connect the serial cable's TX (White), RX (Green), and Ground (Black) wires to the 3 pins next to the ethernet ports as shown in the photo and start your terminal program.



Once powered correctly and with the right SD card you should get a login prompt

After logging in you may be asked to create a new username, we recommend **pi** - if our instructions end up adding gpio access for the pi user, you can copy and paste em



Once installed, you may want to enable mDNS so you can `ssh pi@orangepi.local` instead of needing to know the IP address:

- `sudo apt-get install avahi-daemon`

then **reboot**

Connecting using DHCP and SSH

Another option that you may be available to you is to connect using SSH, or Secure Shell. To connect, you will need to have DHCP, or Dynamic Host Configuration Protocol, enabled and configured on your network and look up the IP address assigned to the Orange Pi R1.

By default, most routers have DHCP enabled and some routers will display all of the hosts connected to them through the web configuration panel. If you are able to retrieve the IP address, then you can connect through SSH.

MacOS/Linux

Mac and Linux should have SSH installed by default and you can access it by going to the command line and typing `ssh root@192.168.0.25` if the IP address of your Orange Pi is 192.168.0.25.

Windows

The easiest way to connect with windows is to use a Terminal program called PuTTY from https://www.putty.org (https://adafru.it/EYm).

You can read more about connecting through SSH in our Adafruit's Raspberry Pi Lesson 6. Using SSH (https://adafru.it/jvB) guide. Although this is written for Raspberry Pi, the steps should be the same.

Set your Python install to Python 3 Default

There's a few ways to do this, we recommend something like this

```
sudo apt-get install -y python3 git python3-pip
sudo update-alternatives --install /usr/bin/python python /usr/bin/python2.7 1
sudo update-alternatives --install /usr/bin/python python /usr/bin/python3.5 2
sudo update-alternatives --config python
```

Of course change the version numbers if newer Python is distributed

Install libgpiod

libgpiod is what we use for gpio toggling. To install run this command:

```
sudo apt-get install libgpiod2 python3-libgpiod
pip3 install gpiod
```

After installation you should be able to `import gpiod` from within Python3



Install Required pip3 Modules

For the Orange Pi R1, a couple of pip modules are required to smooth out the installation.

Run the following command.

`sudo pip3 install wheel flask`

Update Your Board and Python

Run the standard updates:

`sudo apt-get update`

`sudo apt-get upgrade`

and

`sudo pip3 install --upgrade setuptools`

Update all your python 3 packages with

`pip3 freeze - local | grep -v '^\-e' | cut -d = -f 1 | xargs -n1 pip3 install -U`

and

```
sudo bash
```

```
pip3 freeze - local | grep -v '^\-e' | cut -d = -f 1 | xargs -n1 pip3 install -U
```

Enable UART, I2C and SPI

A vast number of our CircuitPython drivers use UART, I2C and SPI for interfacing so you'll want to get those enabled.

You only have to do this once per board but by default all three interfaces are disabled!



Install the support software with

```
sudo apt-get install -y python-smbus python-dev i2c-tools
sudo adduser pi i2c
```

Read **/etc/armbian-release** to figure out your board family, in this case its a **sun8i**

Edit **/boot/armbianEnv.txt** and add these lines at the end, adjusting the `overlay_prefix` for your particular board

```
overlay_prefix=sun8i-h3
overlays=uart1 i2c0 spi-spidev usbhost2 usbhost3
param_spidev_spi_bus=1
```

```
overlay_prefix=sun8i-h3
overlays=i2c0 spi-spidev uart1 usbhost2 usbhost3
param_spidev_spi_bus=1
```

Once you're done with both and have rebooted, verify you have the I2C and SPI devices with the command `ls /dev/i2c* /dev/spi*`

You should see at least one i2c device and one spi device

```
pi@orangepi:~$ ls /dev/i2c* /dev/spi*
/dev/i2c-0  /dev/spidev1.0
pi@orangepi:~$
```

```
pi@orangepi:~$ sudo i2cdetect -l
[sudo] password for pi:
i2c-0   i2c             mv64xxx_i2c adapter                 I2C adapter
pi@orangepi:~$
```

```
pi@orangepi:~$ sudo i2cdetect -y 0
     0  1  2  3  4  5  6  7  8  9  a  b  c  d  e  f
00:          -- -- -- -- -- -- -- -- -- -- -- -- --
10: -- -- -- -- -- -- -- -- -- -- -- -- -- -- -- --
20: -- -- -- -- -- -- -- -- -- -- -- -- -- -- -- --
30: -- -- -- -- -- -- -- -- -- -- -- -- -- -- -- --
40: -- -- -- -- -- -- -- -- -- -- -- -- -- -- -- --
50: -- -- -- -- -- -- -- -- -- -- -- -- -- -- -- --
60: -- -- -- -- -- -- -- -- -- -- -- -- -- -- -- --
70: -- -- -- -- -- -- -- 77
pi@orangepi:~$
```

You can test to see what I2C addresses are connected by running `sudo i2cdetect -y 0` (on **PA11/PA12**)

In this case I do have a sensor on the 'standard' i2c port i2c-0 under address 0x77

You can also install WiringOP-Zero and then run `gpio readall` to see the MUX status. If you see **ALT3** next to a pin, it's a plain GPIO. If you see **ALT4** or **ALT5**, its an SPI/I2C/UART peripheral



Install Python libraries

Now you're ready to install all the python support

Run the following command to install **adafruit_blinka**

```
sudo pip3 install adafruit-blinka
```

The computer will install a few different libraries such as `adafruit-pureio` (our ioctl-only i2c library), `spidev` (for SPI interfacing), `Adafruit-GPIO` (for detecting your board) and of course `adafruit-blinka`

That's pretty much it! You're now ready to test.

Create a new file called **blinkatest.py** with **nano** or your favorite text editor and put the following in:

```
import board
import digitalio
```

```
import busio

print("Hello blinka!")

# Try to great a Digital input
pin = digitalio.DigitalInOut(board.PA6)
print("Digital IO ok!")

# Try to create an I2C device
i2c = busio.I2C(board.SCL, board.SDA)
print("I2C ok!")

# Try to create an SPI device
spi = busio.SPI(board.SCLK, board.MOSI, board.MISO)
print("SPI ok!")

print("done!")
```

Save it and run at the command line with

```
sudo python3 blinkatest.py
```

You should see the following, indicating digital i/o, I2C and SPI all worked



Digital I/O

The first step with any new hardware is the 'hello world' of electronics - blinking an LED. This is very easy with CircuitPython and Orange Pi. We'll extend the example to also show how to wire up a button/switch.

Orange Pi (Allwinner) boards don't have any way to set the pullup/pulldown resistors, so you'll need to use external resistors instead of built-in pullups, whenever it makes sense!



Parts Used

Any old LED will work just fine as long as its not an IR LED (you can't see those) and a 470 to 2.2K resistor

Diffused Blue 10mm LED (25 pack)
Need some big indicators? We are big fans of these huge diffused blue LEDs. They are really bright so they can be seen in daytime, and from any angle. They go easily into a breadboard...
https://www.adafruit.com/product/847



Through-Hole Resistors - 470 ohm 5% 1/4W - Pack of 25

ΩMG! You're not going to be able to resist these handy resistor packs! Well, axially, they do all of the resisting for you!This is a 25 Pack of...

https://www.adafruit.com/product/2781

Some tactile buttons or switches

Tactile Switch Buttons (12mm square, 6mm tall) x 10 pack

Medium-sized clicky momentary switches are standard input "buttons" on electronic projects. These work best in a PCB but

https://www.adafruit.com/product/1119

We recommend using a breadboard and some female-male wires.



Premium Female/Male 'Extension' Jumper Wires - 40 x 6" (150mm)

Handy for making wire harnesses or jumpering between headers on PCB's. These premium jumper wires are 6" (150mm) long and come in a 'strip' of 40 (4 pieces of each of...

https://www.adafruit.com/product/826

You can use a Cobbler to make this a little easier, the pins will be labeled according to Raspberry Pi names so just check the Orange Pi name!



Adafruit Pi Cobbler + Kit- Breakout Cable for Pi B+/A+/Pi 2/Pi 3

The Raspberry Pi B+ has landed on the Maker World like a 40-GPIO pinned, quad-USB ported, credit card sized bomb of DIY joy. And while you can use most of our great Model B accessories...
https://www.adafruit.com/product/1990

Assembled Pi T-Cobbler Plus - GPIO Breakout

This is the assembled version of the Pi T-Cobbler Plus. It only works with the Raspberry Pi Model Zero, A+, B+, Pi 2, Pi 3 & Pi 4! (Any Pi with 2x20...
https://www.adafruit.com/product/2028

Wiring

Connect the Orange Pi **Ground** pin to the **blue ground rail** on the breadboard.

- Connect one side of the tactile switch to Orange Pi **GPIO PA6**
- Connect a ~10K pull up resistor from **PA6** to **3.3V**
- Connect the other side of the tactile switch to the **ground** rail
- Connect the longer/positive pin of the LED to Orange Pi **GPIO PD14**
- Connect the shorter/negative pin of the LED to a 470ohm to 2.2K resistor, the other side of the resistor goes to **ground** rail

There's no Orange Pi PC Fritzing object, so we sub'd a Raspberry Pi in



orangepigpio.fzz

https://adafru.it/F0V

Double-check you have the right wires connected to the right location, it can be tough to keep track of Pi pins as there are forty of them!

No additional libraries are needed so we can go straight on to the example code

However, we recommend running a pip3 update!

```
pip3 install --upgrade adafruit_blinka
```

Blinky Time!

The finish line is right up ahead, lets start with an example that blinks the LED on and off once a second (half a second on, half a second off):

```
import time
import board
import digitalio

print("hello blinky!")

led = digitalio.DigitalInOut(board.PD14)
led.direction = digitalio.Direction.OUTPUT

while True:
    led.value = True
    time.sleep(0.5)
```

```
    led.value = False
    time.sleep(0.5)
```

Verify the LED is blinking. If not, check that it's wired to GPIO PD14, the resistor is installed correctly, and you have a Ground wire to the Orange Pi.

Type Control-C to quit

Button It Up

Now that you have the LED working, lets add code so the LED turns on whenever the button is pressed

```
import time
import board
import digitalio

print("press the button!")

led = digitalio.DigitalInOut(board.PD14)
led.direction = digitalio.Direction.OUTPUT

button = digitalio.DigitalInOut(board.PA6)
button.direction = digitalio.Direction.INPUT
# use an external pullup since we don't have internal PU's
#button.pull = digitalio.Pull.UP

while True:
    led.value = not button.value # light when button is pressed!
```

Press the button - see that the LED lights up!

Type Control-C to quit

I2C Sensors & Devices

The most popular electronic sensors use I2C to communicate. This is a 'shared bus' 2 wire protocol, you can have multiple sensors connected to the two SDA and SCL pins as long as they have unique addresses (check this guide for a list of many popular devices and their addresses (https://adafru.it/BK0))

Lets show how to wire up a popular BME280. This sensor provides temperature, barometric pressure and humidity data over I2C

We're going to do this in a lot more depth than our guide pages for each sensor, but the overall technique is basically identical for any and all I2C sensors.

Honestly, the hardest part of using I2C devices is figuring out the I2C address (https://adafru.it/BK0) and which pin is SDA and which pin is SCL!

Don't forget you have to enable I2C overlay

Parts Used



Adafruit BME280 I2C or SPI Temperature Humidity Pressure Sensor
Bosch has stepped up their game with their new BME280 sensor, an environmental sensor with temperature, barometric pressure and humidity! This sensor is great for all sorts...
https://www.adafruit.com/product/2652

We recommend using a breadboard and some female-male wires.



Premium Female/Male 'Extension' Jumper Wires - 40 x 6" (150mm)
Handy for making wire harnesses or jumpering between headers on PCB's. These premium jumper wires are 6" (150mm) long and come in a 'strip' of 40 (4 pieces of each of...
https://www.adafruit.com/product/826

You can use a Cobbler to make this a little easier, the pins are then labeled!



Adafruit Pi Cobbler + Kit- Breakout Cable for Pi B+/A+/Pi 2/Pi 3

The Raspberry Pi B+ has landed on the Maker World like a 40-GPIO pinned, quad-USB ported, credit card sized bomb of DIY joy. And while you can use most of our great Model B accessories...
https://www.adafruit.com/product/1990

Assembled Pi T-Cobbler Plus - GPIO Breakout

This is the assembled version of the Pi T-Cobbler Plus. It only works with the Raspberry Pi Model Zero, A+, B+, Pi 2, Pi 3 & Pi 4! (Any Pi with 2x20...
https://www.adafruit.com/product/2028

Wiring

- Connect the Orange Pi **3.3V** power pin to **Vin**
- Connect the Orange Pi **GND** pin to **GND**
- Connect the Pi **SDA** pin to the BME280 **SDI**
- Connect the Pi **SCL** pin to to the BME280 **SCK**

There's no Orange Pi PC Fritzing object so we're showing Raspberry Pi which has the same pinout



Double-check you have the right wires connected to the right location, it can be tough to keep track of Pi pins as there are forty of them!

After wiring, we recommend running I2C detection with `sudo i2cdetect -y 0` to verify that you see the device, in this case its address **77**

```
root@orangepipc:/home/pi# i2cdetect -y 0
     0  1  2  3  4  5  6  7  8  9  a  b  c  d  e  f
00:          -- -- -- -- -- -- -- -- -- -- -- -- --
10: -- -- -- -- -- -- -- -- -- -- -- -- -- -- -- --
20: -- -- -- -- -- -- -- -- -- -- -- -- -- -- -- --
30: -- -- -- -- -- -- -- -- -- -- -- -- -- -- -- --
40: -- -- -- -- -- -- -- -- -- -- -- -- -- -- -- --
50: -- -- -- -- -- -- -- -- -- -- -- -- -- -- -- --
60: -- -- -- -- -- -- -- -- -- -- -- -- -- -- -- --
70: -- -- -- -- -- -- -- 77
```

Install the CircuitPython BME280 Library

OK onto the good stuff, you can now install the Adafruit BME280 CircuitPython library.

As of this writing, not all libraries are up on PyPI so you may want to search before trying to install. Look for **circuitpython** and then the driver you want.



(If you don't see it you can open up a github issue on circuitpython to remind us (https://adafru.it/tB7)!)

Once you know the name, install it with

```
pip3 install adafruit-circuitpython-bme280
```



You'll notice we also installed a dependancy called **adafruit-circuitpython-busdevice**. This is a great thing about pip, if you have other required libraries they'll get installed too!

We also recommend an adafruit-blinka update in case we've fixed bugs:

```
pip3 install --upgrade adafruit_blinka
```

Run that code!

The finish line is right up ahead. You can now run one of the (many in some cases) example scripts we've written for you.

Check out the examples for your library by visiting the repository for the library and looking in the example folder. In this case, it would be https://github.com/adafruit/Adafruit_CircuitPython_BME280/tree/master/examples (https://adafru.it/BK1)

As of this writing there's only one example. But that's cool, here it is:

```
# SPDX-FileCopyrightText: 2021 ladyada for Adafruit Industries
# SPDX-License-Identifier: MIT

import time
import board
from adafruit_bme280 import basic as adafruit_bme280

# Create sensor object, using the board's default I2C bus.
i2c = board.I2C()  # uses board.SCL and board.SDA
# i2c = board.STEMMA_I2C()  # For using the built-in STEMMA QT connector on a
microcontroller
bme280 = adafruit_bme280.Adafruit_BME280_I2C(i2c)

# OR create sensor object, using the board's default SPI bus.
# spi = board.SPI()
# bme_cs = digitalio.DigitalInOut(board.D10)
# bme280 = adafruit_bme280.Adafruit_BME280_SPI(spi, bme_cs)

# change this to match the location's pressure (hPa) at sea level
bme280.sea_level_pressure = 1013.25

while True:
    print("\nTemperature: %0.1f C" % bme280.temperature)
    print("Humidity: %0.1f %%" % bme280.relative_humidity)
    print("Pressure: %0.1f hPa" % bme280.pressure)
    print("Altitude = %0.2f meters" % bme280.altitude)
    time.sleep(2)
```

Save this code to your Pi by copying and pasting it into a text file, downloading it directly from the Pi, etc.

Then in your command line run

`python3 bme280_simpletest.py`

```
root@orangepipc:/home/pi# python3 bme280test.py

Temperature: 23.9 C
Humidity: 32.6 %
Pressure: 1015.2 hPa
Altitude = -16.39 meters

Temperature: 23.9 C
Humidity: 32.7 %
Pressure: 1015.2 hPa
Altitude = -16.31 meters
^CTraceback (most recent call last):
  File "bme280test.py", line 24, in <module>
    time.sleep(2)
KeyboardInterrupt
root@orangepipc:/home/pi#
```

The code will loop with the sensor data until you quit with a Control-C

That's it! Now if you want to read the documentation on the library, what each function does in depth, visit our readthedocs documentation at

https://circuitpython.readthedocs.io/projects/bme280/en/latest/ (https://adafru.it/BK2)

SPI Sensors & Devices

SPI is less popular than I2C but still you'll see lots of sensors and chips use it. Unlike I2C, you don't have everything share two wires. Instead, there's three shared wires (**clock**, **data in**, **data out**) and then a unique '**chip select**' line for each chip.

The nice thing about SPI is you can have as many chips as you like, even the same kind, all share the three SPI wires, as long as each one has a unique chip select pin.

The formal/technical names for the 4 pins used are:

- SPI clock - called **SCLK**, **SCK** or **CLK**
- SPI data out - called **MOSI** for **M**icrocontroller **O**ut **S**erial **I**n. This is the wire that takes data from the Linux computer to the sensor/chip. Sometimes marked **SDI** or **DI** on chips
- SPI data in - called **MISO** for **M**icrocontroller **I**n **S**erial **O**ut. This is the wire that takes data to the Linux computer from the sensor/chip. Sometimes marked **SDO** or **DO** on chips
- SPI chip select - called **CS** or **CE**

Remember, connect all SCK, MOSI and MISO pins together (unless there's some specific reason/instruction not to) and a unique CS pin for each device.

WARNING! SPI on Linux/Orange PI WARNING!

SPI on microcontrollers is fairly simple, you have an SPI peripheral and you can transfer data on it with some low level command. Its 'your job' as a programmer to control the CS lines with a GPIO. That's how CircuitPython is structured as well. `busio` does just the SPI transmit/receive part and `busdevice` handles the chip select pin as well.

Linux, on the other hand, doesn't let you send data to SPI without a CS line, and the CS lines are fixed in hardware as well. For example on the Orange Pi PC, there's only one CS pins available for the hardware SPI pins - **SPI_CS** known as **PC3** - and you have to use it. (In theory there's an ioctl option called `no_cs` but this does not actually work)

The upshot here is - to let you use more than 1 peripheral on SPI, we decided to **let you use any CS pins** you like, CircuitPython will toggle it the way you expect. But

when we transfer SPI data we always tell the kernel to use **SPI_CS**. **SPI_CS** will toggle like a CS pin, but if we leave it disconnected, its no big deal

The upshot here is basically never connect anything to SPI_CS. Use whatever chip select pin you define in CircuitPython and just leave the **CS** pin alone, it will toggle as if it is the chip select line, completely on its own, so you shouldn't try to use it as a digital input/output/whatever.

Don't forget you have to enable SPI with an overlay!

Parts Used

OK now that we've gone thru the warning, lets wire up an SPI MAX31855 thermocouple sensor, this particular device doesn't have a MOSI pin so we'll not connect it.



Thermocouple Amplifier MAX31855 breakout board (MAX6675 upgrade)
Thermocouples are very sensitive, requiring a good amplifier with a cold-compensation reference. The MAX31855K does everything for you, and can be easily interfaced with any...
https://www.adafruit.com/product/269

Thermocouple Type-K Glass Braid Insulated
Thermocouples are best used for measuring temperatures that can go above 100 °C. This is a bare wires bead-probe which can measure air or surface temperatures. Most inexpensive...
https://www.adafruit.com/product/270

We recommend using a breadboard and some female-male wires.



Premium Female/Male 'Extension' Jumper Wires - 40 x 6" (150mm)
Handy for making wire harnesses or jumpering between headers on PCB's. These premium jumper wires are 6" (150mm) long and come in a 'strip' of 40 (4 pieces of each of...
https://www.adafruit.com/product/826

You can use a Cobbler to make this a little easier, the pins are then labeled!



Adafruit Pi Cobbler + Kit- Breakout Cable for Pi B+/A+/Pi 2/Pi 3
The Raspberry Pi B+ has landed on the Maker World like a 40-GPIO pinned, quad-USB ported, credit card sized bomb of DIY joy. And while you can use most of our great Model B accessories...
https://www.adafruit.com/product/1990

Assembled Pi T-Cobbler Plus - GPIO Breakout
This is the assembled version of the Pi T-Cobbler Plus. It only works with the Raspberry Pi Model Zero, A+, B+, Pi 2, Pi 3 & Pi 4! (Any Pi with 2x20...
https://www.adafruit.com/product/2028

Wiring

- Connect the Orange Pi **3.3V** power pin to **Vin**
- Connect the Orange Pi **GND** pin to **GND**
- Connect the Pi **SCLK** pin to the MAX31855 **CLK**
- Connect the Pi **MISO** pin to to the MAX31855 **DO**
- Connect the Pi **GPIO PA7** pin to to the MAX31855 **CS**

There's no Orange Pi PC Fritzing object, so we'll show using a Raspberry Pi which has the same pinout



Double-check you have the right wires connected to the right location, it can be tough to keep track of Pi pins as there are forty of them!

Install the CircuitPython MAX31855 Library

OK onto the good stuff, you can now install the Adafruit MAX31855 CircuitPython library.

As of this writing, not all libraries are up on PyPI so you may want to search before trying to install. Look for **circuitpython** and then the driver you want.

(If you don't see it [you can open up a github issue on circuitpython to remind us (https://adafru.it/tB7)](https://adafru.it/tB7)!)

Once you know the name, install it with

```
pip3 install adafruit-circuitpython-max31855
```



You'll notice we also installed a few other dependancies called **spidev**, **adafruit-pureio**, **adafruit-circuitpython-busdevice** and more. This is a great thing about pip, if you have other required libraries they'll get installed too!

We also recommend an adafruit-blinka update in case we've fixed bugs:

```
pip3 install --upgrade adafruit_blinka
```

Run that code!

The finish line is right up ahead. You can now run one of the (many in some cases) example scripts we've written for you.

Check out the examples for your library by visiting the repository for the library and looking in the example folder. In this case, it would be https://github.com/adafruit/Adafruit_CircuitPython_MAX31855/tree/master/examples (https://adafru.it/BKj)

As of this writing there's only one example. But that's cool, here it is:

```
# SPDX-FileCopyrightText: 2021 ladyada for Adafruit Industries
# SPDX-License-Identifier: MIT

import time
```

```
import board
import digitalio
import adafruit_max31855

spi = board.SPI()
cs = digitalio.DigitalInOut(board.D5)

max31855 = adafruit_max31855.MAX31855(spi, cs)
while True:
    tempC = max31855.temperature
    tempF = tempC * 9 / 5 + 32
    print("Temperature: {} C {} F ".format(tempC, tempF))
    time.sleep(2.0)
```

Save this code to your Pi by copying and pasting it into a text file, downloading it directly from the Pi, etc.

Change the line that says

`cs = digitalio.DigitalInOut(board.D5)`

to

`cs = digitalio.DigitalInOut(board.PA7)`

Then in your command line run

`python3 max31855_simpletest.py`



The code will loop with the sensor data until you quit with a Control-C

Make sure you have a K-type thermocouple installed into the sensor breakout or you will get an error like the one below!

```
pi@devpi: ~
pi@devpi:~ $ python max31855_simpletest.py
Traceback (most recent call last):
  File "max31855_simpletest.py", line 13, in <module>
    tempC = max31855.temperature
  File "/home/pi/.local/lib/python3.5/site-packages/adafruit_max31855.py", line
86, in temperature
    return self._read() / 4
  File "/home/pi/.local/lib/python3.5/site-packages/adafruit_max31855.py", line
69, in _read
    raise RuntimeError("thermocouple not connected")
RuntimeError: thermocouple not connected
pi@devpi:~ $
```

That's it! Now if you want to read the documentation on the library, what each function does in depth, visit our readthedocs documentation at

https://circuitpython.readthedocs.io/projects/max31855/en/latest/ (https://adafru.it/BKk)

UART / Serial

After I2C and SPI, the third most popular "bus" protocol used is serial (also sometimes referred to as 'UART'). This is a non-shared two-wire protocol with an RX line, a TX line and a fixed baudrate. The most common devices that use UART are GPS units, MIDI interfaces, fingerprint sensors, thermal printers, and a scattering of sensors.

One thing you'll notice fast is that most linux computers have minimal UARTs, often only 1 hardware port. And that hardware port may be shared with a console.

There are two ways to connect UART / Serial devices to your Orange Pi. The easy way, and the hard way.

We'll demonstrate wiring up & using an Ultimate GPS with both methods



Adafruit Ultimate GPS Breakout - 66 channel w/10 Hz updates
We carry a few different GPS modules here in the Adafruit shop, but none that satisfied our every desire - that's why we designed this little GPS breakout board. We believe this is...
https://www.adafruit.com/product/746

The Easy Way - An External USB-Serial Converter

By far the easiest way to add a serial port is to use a USB to serial converter cable or breakout. They're not expensive, and you simply plug it into the USB port. On the other end are wires or pins that provide power, ground, RX, TX and maybe some other control pads or extras.

Here are some options, they have varying chipsets and physical designs but all will do the job. We'll list them in order of recommendation.

The first cable is easy to use and even has little plugs that you can arrange however you like, it contains a CP2102

USB to TTL Serial Cable - Debug / Console Cable for Raspberry Pi
The cable is easiest way ever to connect to your microcontroller/Raspberry Pi/WiFi router serial console port. Inside the big USB plug is a USB<->Serial conversion chip and at...
https://www.adafruit.com/product/954

The CP2104 Friend is low cost, easy to use, but requires a little soldering, it has an '6-pin FTDI compatible' connector on the end, but all pins are broken out the sides



Adafruit CP2104 Friend - USB to Serial Converter
Discontinued - you can grab Adafruit CP2102N Friend - USB to Serial Converter instead! Long gone are...
https://www.adafruit.com/product/3309

Both the FTDI friend and cable use classic FTDI chips, these are more expensive than the CP2104 or PL2303 but sometimes people like them!



FTDI Friend with Micro USB Port + extras

Long gone are the days of parallel ports and serial ports. Now the USB port reigns supreme! But USB is hard, and you just want to transfer your every-day serial data from a...

https://www.adafruit.com/product/284

FTDI Serial TTL-232 USB Cable

Just about all electronics use TTL serial for debugging, bootloading, programming, serial output, etc. But it's rare for a computer to have a serial port anymore. This is a USB to...

https://www.adafruit.com/product/70

You can wire up the GPS by connecting the following

- **GPS Vin** to **USB 5V** or **3V** (red wire on USB console cable)
- **GPS Ground** to **USB Ground** (black wire)
- **GPS RX** to **USB TX** (green wire)
- **GPS TX** to **USB RX** (white wire)



Once the USB adapter is plugged in, you'll need to figure out what the serial port name is. You can figure it out by unplugging-replugging in the USB and then typing `dmesg | tail -10` (or just `dmesg`) and looking for text like this:

```
pi@devpi:~ $ dmesg | tail -10
[  601.391424] usb 1-1.2: Manufacturer: FTDI
[  601.391432] usb 1-1.2: SerialNumber: AL00FP25
[  601.440489] usbcore: registered new interface driver usbserial
[  601.440554] usbcore: registered new interface driver usbserial_generic
[  601.440609] usbserial: USB Serial support registered for generic
[  601.455895] usbcore: registered new interface driver ftdi_sio
[  601.455970] usbserial: USB Serial support registered for FTDI USB Serial Device
[  601.456248] ftdi_sio 1-1.2:1.0: FTDI USB Serial Device converter detected
[  601.456383] usb 1-1.2: Detected FT232RL
[  601.459259] usb 1-1.2: FTDI USB Serial Device converter now attached to ttyUSB0
```

At the bottom, you'll see the 'name' of the attached device, in this case its `ttyUSB0`, that means our serial port device is available at `/dev/ttyUSB0`

The Hard Way - Using Built-in UART

If you don't want to plug in external hardware to the Pi you can use the built in UART on the RX/TX pins. Unlike the Raspberry Pi, the Orange Pi isn't using the RX/TX pins for a console, those are on a different UART peripheral, so as long as you've activated UART3 (see the Install page) you should be good to go!

You can use the built in UART via `/dev/ttyS3`

Wire the GPS as follows:

> There's no Orange Pi Fritzing object, but the Raspberry Pi has the same pinout so we're using that instead



Install the CircuitPython GPS Library

OK onto the good stuff, you can now install the Adafruit GPS CircuitPython library.

As of this writing, not all libraries are up on PyPI so you may want to search before trying to install. Look for **circuitpython** and then the driver you want.



(If you don't see it you can open up a github issue on circuitpython to remind us (https://adafru.it/tB7)!)

Once you know the name, install it with

```
pip3 install pyserial adafruit-circuitpython-gps
```

You'll notice we also installed a dependancy called **pyserial**. This is a great thing about pip, if you have other required libraries they'll get installed too!

We also recommend an adafruit-blinka update in case we've fixed bugs:

```
pip3 install --upgrade adafruit_blinka
```

Run that code!

The finish line is right up ahead. You can now run one of the (many in some cases) example scripts we've written for you.

Check out the examples for your library by visiting the repository for the library and looking in the example folder. In this case, it would be https://github.com/adafruit/Adafruit_CircuitPython_GPS/tree/master/examples (https://adafru.it/Ca9)

Lets start with the simplest, the echo example

```
# SPDX-FileCopyrightText: 2021 ladyada for Adafruit Industries
# SPDX-License-Identifier: MIT

# Simple GPS module demonstration.
```

```
# Will print NMEA sentences received from the GPS, great for testing connection
# Uses the GPS to send some commands, then reads directly from the GPS
import time
import board
import busio

import adafruit_gps

# Create a serial connection for the GPS connection using default speed and
# a slightly higher timeout (GPS modules typically update once a second).
# These are the defaults you should use for the GPS FeatherWing.
# For other boards set RX = GPS module TX, and TX = GPS module RX pins.
uart = busio.UART(board.TX, board.RX, baudrate=9600, timeout=10)

# for a computer, use the pyserial library for uart access
# import serial
# uart = serial.Serial("/dev/ttyUSB0", baudrate=9600, timeout=10)

# If using I2C, we'll create an I2C interface to talk to using default pins
# i2c = board.I2C()  # uses board.SCL and board.SDA
# i2c = board.STEMMA_I2C()  # For using the built-in STEMMA QT connector on a
microcontroller

# Create a GPS module instance.
gps = adafruit_gps.GPS(uart)  # Use UART/pyserial
# gps = adafruit_gps.GPS_GtopI2C(i2c)  # Use I2C interface

# Initialize the GPS module by changing what data it sends and at what rate.
# These are NMEA extensions for PMTK_314_SET_NMEA_OUTPUT and
# PMTK_220_SET_NMEA_UPDATERATE but you can send anything from here to adjust
# the GPS module behavior:
#   https://cdn-shop.adafruit.com/datasheets/PMTK_A11.pdf

# Turn on the basic GGA and RMC info (what you typically want)
gps.send_command(b"PMTK314,0,1,0,1,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0")
# Turn on just minimum info (RMC only, location):
# gps.send_command(b'PMTK314,0,1,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0')
# Turn off everything:
# gps.send_command(b'PMTK314,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0')
# Tuen on everything (not all of it is parsed!)
# gps.send_command(b'PMTK314,1,1,1,1,1,1,0,0,0,0,0,0,0,0,0,0,0,0,0')

# Set update rate to once a second (1hz) which is what you typically want.
gps.send_command(b"PMTK220,1000")
# Or decrease to once every two seconds by doubling the millisecond value.
# Be sure to also increase your UART timeout above!
# gps.send_command(b'PMTK220,2000')
# You can also speed up the rate, but don't go too fast or else you can lose
# data during parsing.  This would be twice a second (2hz, 500ms delay):
# gps.send_command(b'PMTK220,500')

# Main loop runs forever printing data as it comes in
timestamp = time.monotonic()
while True:
    data = gps.read(32)  # read up to 32 bytes
    # print(data)  # this is a bytearray type

    if data is not None:
        # convert bytearray to string
        data_string = "".join([chr(b) for b in data])
        print(data_string, end="")

    if time.monotonic() - timestamp > 5:
        # every 5 seconds...
        gps.send_command(b"PMTK605")  # request firmware version
        timestamp = time.monotonic()
```

We'll need to configure this code to work with our UART port name.

- If you're using a USB-to-serial converter, the device name is probably `/dev/ttyUSB0` - but check `dmesg` to make sure
- If you're using the built-in UART on the Orange Pi PC, the device name is `/dev/ttyS3`

Comment out the lines that reference `board.TX`, `board.RX` and `busio.uart` and uncomment the lines that `import serial` and define the `serial` device, like so:

```
# Define RX and TX pins for the board's serial port connected to the GPS.
# These are the defaults you should use for the GPS FeatherWing.
# For other boards set RX = GPS module TX, and TX = GPS module RX pins.
#RX = board.RX
#TX = board.TX

# Create a serial connection for the GPS connection using default speed and
# a slightly higher timeout (GPS modules typically update once a second).
#uart = busio.UART(TX, RX, baudrate=9600, timeout=3000)

# for a computer, use the pyserial library for uart access
import serial
uart = serial.Serial("/dev/ttyUSB0", baudrate=9600, timeout=3000)
```

And update the `"/dev/ttyUSB0"` device name if necessary to match your USB interface

Whichever method you use, you should see output like this, with **$GP** "NMEA sentences" - there probably wont be actual location data because you haven't gotten a GPS fix. As long as you see those **$GP** strings sorta like the below, you've got it working!



More To Come!

That's just a taste of what we've got working so far

We're adding more support constantly, so please hold tight and visit the adafruit_blinka github repo (https://adafru.it/BJX) to share your feedback and perhaps even submit some improvements!

If you'd like to contribute, but aren't sure where to start, check out the following guides:

- Adding a Single Board Computer to PlatformDetect for Blinka (https://adafru.it/JFy)
- Adding a Single Board Computer to Blinka (https://adafru.it/KEF)

FAQ & Troubleshooting

There's a few oddities when running Blinka/CircuitPython on linux. Here's a list of stuff to watch for that we know of!

This FAQ covers all the various platforms and hardware setups you can run Blinka on. Therefore, some of the information may not apply to your specific setup.

Update Blinka/Platform Libraries

Most issues can be solved by forcing Python to upgrade to the latest `blinka` / `platform-detect` libraries. Try running

```
sudo python3 -m pip install --upgrade --force-reinstall adafruit-blinka Adafruit-PlatformDetect
```

Getting an error message about "board" not found or "board" has no attribute

Somehow you have ended up with either the wrong **board** module or no **board** module at all.

DO NOT try to fix this by manually installing a library named `board`. There is one out there (https://adafru.it/NCE) and it has nothing to do with Blinka. You will break things if you install that library!

The easiest way to recover is to simply force a reinstall of Blinka with:

```
python3 -m pip install --upgrade --force-reinstall adafruit-blinka
```

Mixed SPI mode devices

Due to the way we share an SPI peripheral, you cannot have two SPI devices with different 'mode/polarity' on the same SPI bus - you'll get weird data

95% of SPI devices are mode 0, check the driver to see mode or polarity settings. For example:

- LSM9DS1 is mode 1 (https://adafru.it/NCF), please use in I2C mode instead of SPI
- MAX31865 is phase 1 (https://adafru.it/NCG), try using this on a separate SPI device, or read data twice.

Why am I getting AttributeError: 'SpiDev' object has no attribute 'writebytes2'?

This is due to having an older version of spidev (https://adafru.it/JEi). You need at least version 3.4. This should have been taken care of (https://adafru.it/NCH) when you installed Blinka, but in some cases it does not seem to happen.

To check what version of spidev Python is using:

```
$ python3
Python 3.6.8 (default, Oct 7 2019, 12:59:55)
[GCC 8.3.0] on linux
Type "help", "copyright", "credits" or "license" for more
information.
>>> import spidev
>>> spidev.__version__
'3.4'
>>>
```

If you see a version lower then 3.4 reported, then try a force upgrade of spidev with (back at command line):

```
sudo python3 -m pip install --upgrade --force-reinstall spidev
```

No Pullup/Pulldown support on some linux boards or MCP2221

Some linux boards, for example, AllWinner-based, do not have support to set pull up or pull down on their GPIO. Use an external resistor instead!

Getting OSError: read error with MCP2221

If you are getting a stack trace that ends with something like:

```
return self._hid.read(64)
File "hid.pyx", line 122, in hid.device.read
OSError: read error
```

Try setting an environment variable named **BLINKA_MCP2221_RESET_DELAY** to a value of **0.5 or higher**.

Windows:

```
set BLINKA_MCP2221_RESET_DELAY=0.5
```

Linux:

```
export BLINKA_MCP2221_RESET_DELAY=0.5
```

This is a value in seconds to wait between resetting the MCP2221 and the attempt to reopen it. The reset is seen by the operating system as a hardware disconnect/reconnect. Different operating systems can need different amounts of time to wait after the reconnect before the attempt to reopen. Setting the above environment variable will override the default reset delay time, allowing it to be increased as needed for different setups.

Using FT232H with other FTDI devices.

Blinka uses the libusbk driver to talk to the FT232H directly. If you have other FTDI devices installed that are using the FTDI VCP drivers, you may run into issues. See here for a possible workaround:

https://forums.adafruit.com/viewtopic.php?f=19&t=166999 (https://adafru.it/doW)

Getting "no backend available" with pyusb on Windows

This is probably only an issue for older versions of Windows. If you run into something like this, see this issue thread:

https://github.com/pyusb/pyusb/issues/120 (https://adafru.it/Uao)

which describes copying the 32bit and 64bit DLLs into specific folders. (example for Win7 (https://adafru.it/Uao))

Getting "no backend available" or other problems with pyusb on Mac

Check out this issue thread:

https://github.com/pyusb/pyusb/issues/355 (https://adafru.it/19fh)

which has **lots** of discussion. It is probably worth reading through it all to determine what applies for your setup. Most solutions seem to rely on setting the **DYLD_LIBRARY_PATH** environment variable.

This issue thread has further information:

https://github.com/orgs/Homebrew/discussions/3424 (https://adafru.it/19fi)

I can't get neopixel, analogio, audioio, rotaryio, displayio or pulseio to work!

Some CircuitPython modules like may not be supported.

- Most SBCs do not have analog inputs so there is no `analogio`
- Few SBCs have `neopixel` support so that is only available on Raspberry Pi (and any others that have low level neopixel protocol writing
- Rotary encoders (`rotaryio`) is handled by interrupts on microcontrollers, and is not supported on SBCs at this time
- Likewise `pulseio` PWM support is not supported on many SBCs, and if it is, it will not support a carrier wave (Infrared transmission)
- For display usage, we suggest using python `Pillow` library or `Pygame` , we do not have `displayio` support

We aim to have, at a minimum, `digitalio` and `busio` (I2C/SPI). This lets you use the vast number of driver libraries

For analog inputs, the MCP3xxx library (https://adafru.it/CPN) will give you `AnalogIn` objects. For PWM outputs, try the PCA9685 (https://adafru.it/tZF). For audio, use pygame or other Python3 libraries to play audio.

Some libraries, like Adafruit_CircuitPython_DHT (https://adafru.it/Beq) will try to bit-bang if pulsein isn't available. Slow linux boards (<700MHz) may not be able to read the pins fast enough), you'll just have to try!

Help, I'm getting the message "error while loading shared libraries: libgpiod.so.2: cannot open shared object file: No such file or directory"

It looks like **libgpiod** may not be installed on your board.

Try running the command: `sudo apt-get install libgpiod2`

= v5.5.0""> When running the libgpiod script, I see the message: configure: error: "libgpiod needs linux headers version >= v5.5.0"

Be sure you have the latest libgpiod.py script and run it with the `-l` or `--legacy` flag:

```
sudo python3 libgpiod.py --legacy
```



All Raspberry Pi Computers Have:

1 x I2C port with **busio** (but clock stretching is not supported in hardware, so you must set the I2C bus speed to 10KHz to 'fix it')
2 x SPI ports with **busio**
1 x UART port with **serial** - note this is shared with the hardware console
pulseio.pulseIn using gpiod
neopixel support on a few pins
No AnalogIn support (Use an MCP3008 or similar to add ADC)
No PWM support (Use a PCA9685 or similar to add PWM)



Google Coral TPU Dev Boards Have:

1 x I2C port with **busio**
1 x SPI ports with **busio**
1 x UART port with **serial** - note this is shared with the hardware console
3 x PWMOut support
No NeoPixel support
No AnalogIn support (Use an MCP3008 or similar to add ADC)



Orange Pi PC Plus Boards Have:

1 x I2C port with **busio**
1 x SPI ports with **busio**
1 x UART port with **serial**
No NeoPixel support
No AnalogIn support (Use an MCP3008 or similar to add ADC)
No PWM support (Use a PCA9685 or similar to add PWM)



Orange Pi R1 Boards Have:

1 x I2C port with **busio**
1 x SPI port with **busio**
1 x UART port with **serial**
No NeoPixel support
No AnalogIn support (Use an MCP3008 or similar to add ADC)
No PWM support (Use a PCA9685 or similar to add PWM)



ODROID C2 Boards Have:

1 x I2C port with **busio**
No SPI support
1 x UART port with **serial** - note this is shared with the hardware console
No NeoPixel support
No AnalogIn support (Use an MCP3008 or similar to add ADC)
No PWM support (Use a PCA9685 or similar to add PWM)



DragonBoard 410c Boards Have:

2 x I2C port with **busio**
1 x SPI port with **busio**
1 x UART port with **serial**
No NeoPixel support
No AnalogIn support (Use an MCP3008 or similar to add ADC)
No PWM support (Use a PCA9685 or similar to add PWM)



NVIDIA Jetson Nano Boards Have:

2 x I2C port with **busio**
2 x SPI ports with **busio**
2 x UART port with **serial** - note one of these is shared with the hardware console
No NeoPixel support
No AnalogIn support (Use an MCP3008 or similar to add ADC)
No PWM support (Use a PCA9685 or similar to add PWM)



FT232H Breakouts Have:

1x I2C port **OR** SPI port with **busio**
12x GPIO pins with **digitalio**
No UART
No AnalogIn support
No AnalogOut support
No PWM support
If you are using Blinka in FT232H mode (https://adafru.it/FWD), then keep in mind these basic limitations.

SPI and I2C can not be used at the same time since they share the same pins.
GPIO speed is not super fast, so trying to do arbitrary bit bang like things may run into speed issues.
There are no ADCs.
There are no DACs.
UART is not available (its a different FTDI mode)



MCP2221 Breakouts Have:

1x I2C port with **busio**
4x GPIO pins with **digitalio**
3x AnalogIn with **analogio**
1x AnalogOut with **analogio**
1x UART with **pyserial**
No PWM support
No hardware SPI support
If you are using Blinka in MCP2221 mode, then keep in mind these basic limitations.

GPIO speed is not super fast, so trying to do arbitrary bit bang like things may run into speed issues.
UART is available via `pyserial`, the serial COM port shows up as a second USB device during enumeration